



























































your personal fabric selector

	2500 mm	127 mm	89 mm	63 mm	Openness Factor %	Optical Transmittance %	Ultraviolet Protection %	Absorption %	Solar Reflection %
White					1	17	99	13	67
					3	20	96	12	66
Beige					1	13	99	24	60
					3	16	96	24	56
Light Grey					1	8	99	39	49
					3	11	96	34	51
Mid Grey					1	3	99	57	36
					3	6	97	53	37
Dark Grey					1	1	99	88	12
					3	4	97	83	13
Bronze					1	1	99	93	7
					3	4	96	88	8
Charcoal					1	1	99	96	4
					3	4	96	93	3



roe fabric

Roe fabric is designed for areas where a high level of solar control is required along with exceptional performance characteristics. Whilst reducing solar glare, the comfort of natural light is still maintained. With 6 colours along with one of the most advanced production procedures, the Flame Retardant fabric is designed with the commercial, educational and healthcare environments in mind.

Fabric Composition:	70% PVC, 30% Polyester
Fabric Range:	7
Louvre Widths:	127mm (5") / 89mm (3.5") / 63mm (2.5")
Louvre Roll Length:	30m
Roller Fabric Width:	2500mm (98 ¹ / ₂ ")
Roller Fabric Length:	30m
Fabric Thickness:	0.50mm
Fabric Weight:	400 g/m ²
Fire Retardancy:	BS5867 Part 2, Type B
Shading:	High Performance Screen. Suitable for computer environments
Moisture Resistance:	Suitable for moist conditions
Care Instructions:	Wipe clean
Mesh/in:	48 x 48
Colour Fastness:	4.5